



INSTITUT NANOSCIENCES
ET CRYOGÉNIE

la recherche, ressource fondamentale
research - a fundamental resource

SBT | SCIB | SPINTEC | SPRAM | SPSMS | SP2M

inac.cea.fr



HiPER WP15

SBT Approach

Didier GUILLAUME



3rd European Target Fabrication Workshop - Oxford

HiPER cryogenic design


From ideas

WP15

to first plans



**NUCLEAR
PLANT**



Our guides: SAFETY PRINCIPLES

Radiologic risk have to be controlled

during all the time life

FOR

Workers,

Everyone

To reach this goal we set some

Nature

Safety Important Functions

including

Safety Important Elements

Confinement control

Static confinement

(process, cryostat, Gloves Box, cells)


Dynamic confinement

(Ventilation..)


Radiation limitation

Radiation measurements & protection, Using rules...

One exemple: ventilation





One example: ventilation




GB Ventilation sketch

→ Air



Target factory operating laboratories

1/ Injection ($L = 60 \text{ m} - 320 \text{ m}^2$)



GB Cooling injection pipe ($L \times l \times h = 55 \times 1 \times 1 = 55 \text{ m}^3 \text{ TBD}$)

GB target provider ($L \times l \times h = 2 \times 1 \times 1 = 2 \text{ m}^3 \text{ TBD}$)


GB injector ($L \times l \times h = 3 \times 2 \times 3 = 12 \text{ m}^3 \text{ TBD}$)

GB sabot ($L \times l \times h = 2 \times 2 \times 2 = 8 \text{ m}^3 \text{ TBD}$)

GB wastes ($L \times l \times h = 1 \times 1 \times 1 = 1 \text{ m}^3 \text{ TBD}$)

Target factory operating laboratories

2/ target layering (80 m2)



Access transfert cryostat

(L x l x h = 1 x 1 x 1 = 1m³ TBD)

GB target filling

(L x l x h = 2 x 2 x 2 = 8m³ TBD)

GB conformation cryostat

(L x l x h = 2 x 2 x 3 = 12m³ TBD)

GB collector

(L x l x h = 2 x 2 x 2 = 8 m³ TBD)


Access for control

(L x l x h = 1 x 1 x 1 = 1 m³ TBD)

From Lebedev physical institute developments

Target factory operating laboratories

3/ Target filling (80m2)



Access transfert vessel

(L x l x h = 1 x 1 x 1 = 1m3 TBD)

GB cryocompressor HP 600 atm

(L x l x h = 2 x 2 x 1 = 4m3 TBD)

GB filling cells HP 600 atm & cooling down

(L x l x h = 2 x 2 x 2 = 8m3 TBD)

& GB Cryogenic target recovery

(L x l x h = 2 x 4 x 3 = 24m3 TBD)

Target filling : some target elements


Balloon

Rext	1,023E-03	m
Rint	1,02E-03	m
thickness	3,0E-06	m
inner volume	4,45E-09	m ³
mass	4,130E-08	kg

target

Rext	1,020E-03	m
Rint	8,330E-04	m
thickness	1,9E-04	m
ice volume	2,024E-09	m ³
mass	5,121E-07	kg
or	2,267E-06	m ³ TPN

So the filling pressure is: 510 bars



Target D- T 50-50
mass T2 3,146E-07 kg

Target H - D- T x - x - 70
mass T2 4,404E-07 kg

T2 Budget: 2target 50-50 + 98 target HDT
mass T2 4,4E-05 kg
or 1,6E+13 Bq

We still have to take into account all the dead space

Target filling : balloon thickness vs filling time

Perméation microballon

Valeur fin rampe

Ecart de pression de rupture

Consigne atteinte en

Pression interne (bars)

D/e = 97

20,576 Delta (bars)

16105 s


493,55 Soit un écart de 16,448 bars

Pressions externe et interne identiques à

98 % au bout de 16354 secondes

e (µm)
φ ext (µm)
K (mol/(m.s.Pa))
T (°C)
Premplissage (bars)
dP/dt (bars/min)

25
2430
7,50E-15
20
510
1,9




Based on CHx ballon calculation

HiPER target type:


diameter 2,43 mm
hot gas filling through balloon
pressure 510 bars
with DP < 80 % ballon resistance limit

Balloon thickness micro meter	filling speed bar/mn	time to 510 bars s	int = 98% ext s	DP max < 80% rupt limit bar
1	1,6	19125	19125	0,6
3	1,7	18000	18001	1,8
10	1,8	17000	17001	6,4
25	1,9	16105	16354	20,6
50	2	15300	16434	38,7
100	2,3	13304	16489	65,6
200	3,1	9871	18250	130

Target life time : process overview



Tritium pollution: T2 $\Rightarrow$ He3 evolution



Target factory operating laboratories

4/ Thermal & optic analysis (8 x 7 = 56m²)

Access transfert vessel



(L x l x h = 1 x 1 x 1 = 1m³ TBD)

GB Tools, support and cooling

(L x l x h = 3 x 2 x 2 = 12m³ TBD)

GB Analysis

(L x l x h = 2 x 2 x 2 = 8m³ TBD)



From SBT developments

LMJ target factory in Valduc center

Target factory operating laboratories

5/ R&D lab

Improve HiPER process

T2 test for continuous 10 Hz process

- other process than permeation (liquid filling?)
- permeation still possible but targetry have to manage about 8 hours complete process (+ recycling time)

reducing process time

LHe instead cryocooler, 2 cryocomp. for each cell...


> 350 000 targets

bigger, parallel & redundancy for continuous operating


Nuclear Plant includes ancillary systems

Some place.....	And functions	TBD
Tritium storage	Remote control	
Tritium treatment	Fluids	
Vacuum,	Ventilation	
Wastes	Vacuum,	
Radiation control, analysis	Wastes	
Control room		
Access, offices, maintenance laboratories and meeting room		


HiPER first drawing




Targetry first level:



Targetry ground level:



Targetry second level:



Targetry budget elements:

burst chamber: 10 m diameter	targetry	2380 m2
building chamber: 64 m diameter	Chamber building	5776 m2
	NUCLEAR PLANT:	8156 m2/ level

HiPER tritium budget about 50 g

Targetry Total area	7143 m2
Survey area	2161 m2
controlled area	1441 m2
Active laboratories	1609 m2
Gloves boxes	324 m3

GB ventilation	3200 m3/h
Ventilation in	150 000 m3/h
out	100 000 m3/h
Pelec total	800 kW
Safety	200 kW

Budget about : 70 M€

Studies	3%
building	24%
equipment	38%
fluids	35%

Rough estimation based on our latest french tritium nuclear plant modification