

High-energy multi-pass amplifier design for the PENELOPE laser project


D. Albach, M. Loeser, M. Siebold , F. Roeser, U. Schramm



Helmholtz-Zentrum Dresden - Rossendorf (HZDR)

26/27/28/ March 2014

HEC-DPSSL

Lady Margaret Hall, Oxford





$$\tau_{rad} \approx 2.4ms$$

$$k \approx 9 Wm^{-1}K^{-1}$$

$$n_0^{1\mu m} \approx 1.42$$


$$\left. \frac{dn}{dT} \right|_{300K} \approx -18 \times 10^{-6} K^{-1}$$

$$\left. \frac{dL}{dT} \right|_{300K} \approx 19 \times 10^{-6} K^{-1}$$


Yb^{3+} doped CaF_2 supports short pulse laser operation
(100fs to 150fs on the 100J scale possible)


However : relatively small emission cross sections (small SSG)
 many extraction passes needed

Small Signal Gain for 10J+ amplifiers < 1.3




- up to 1J, 10Hz possible
- thermal aberrations by edge effects (1D → 2D) (e.g. disc bending, stress birefr.)
- scalability: *number of large aperture mirrors*
- damage issues (*pulse overlap, glue, interferences*)
- MP pumping increases efficiency @ RT







- tested at 60J, 10Hz (LLNL) & 10J, 6Hz (RAL)
- low thermal aberrations
- *operation at RT + MP pumping possible*
- pump & extraction from both sides
- 4 slabs 55/110 mm diameter, thickness: 5mm



Multiple slab amplifier design for 10J+ and 100J+ stage



- **Small beam** (e.g. $< 10\text{mm}$) \rightarrow „**Gaussian**“ beam (free propagation)
- **Larger beams** are **cost** intensive (large optics), so:
 - High SSG (> 3) \rightarrow few passes, free propagation
 - Low SSG (< 2) \rightarrow many passes, expensive obviously
- **PENELOPE** case: low SSG (< 1.3), **25mm** beam diameter
 - Reduce beam size to a minimum (serrated aperture)
 - Relay Imaging (4f-telescopes), magnification 1.35



We need about **12 passes** – **B-Integral** important

- **B-Integral**

- Avoid high B (small ripple growth, uncompressed phase...)
- Beam transport at air – no good idea (image relay foci)
- Separate vacuum tubes for each pass → interfaces + material ($B > 1.5$)

→ Put everything in **vacuum**


- no separate windows for vacuum tubes
- “no” **dust**, no air **fluctuations**

But: more bulky, less easy to manipulate,...

+ **replace lenses by spherical mirrors**


- less ghosts, less material


→ $B < 0.5$






Vacuum vessel









All reflective transport optics setup

- less surfaces
- no material dispersion
- no ghosts




12 passes

- magnification 1.35
- Fully image relayed
- Fully reflective
- 6m long







Sketch



6 Rings
75 mirrors in total
Custom tailored

Workshop







No low frequency eigenmodes <50Hz

Fixing is foreseen → reduction in vibration amplitude

- Astigmatism is added with each pass
 - due to spherical mirrors + coupling in and out
 - added components turn with the rotation angle with each pass
 - after full rotation on the ring → defocus component
- Second arm is pure image relay
 - detuning the distance used to introduce defined defocus → defoc „0“
- Full amplifier w. 12 passes
 - Transmission ~80% (coating)
 - Wavefront error <0.12 waves PtV
 - Strehl ratio >0.98
 - adaptive optics?



Partial pumping will lead to a transverse thermal gradient




- thermal lens
- mechanical

$$f_{th} = \frac{p^2}{2d \frac{dn}{dT} \Delta T} \quad \frac{dn}{dT} \approx -\frac{dL}{dT}$$


$$f_{mech} \approx \frac{p^2}{2d \frac{dL}{dT} \Delta T}$$

→ partial compensation is possible

Gas flow drags heat with it




- temperature distribution more complicated
- under observation



Depolarization loss increases with pump power and number of passes
 → sufficiently compensated using a wave plate



lower frame construction



first chamber test


Currently: put it on the table + vacuum tests



3 of 6 modules on the table



Finishing vacuum installation during April

Schematic overview over the 100J+ amp



Vacuum chamber and extraction scheme designed by HZDR:

- 1.2 MW pump peak power @ 980nm
- 80mm laser beam diameter
- 1:1.5 magnification
- 12 passes
- 13m, 20m³ vacuum chamber



10J+ amplifier section :

25mm laser beam diameter

4 slabs, He gas cooled

SSG <1.3 per pass

SR 0.9+

Fully image relayed 12 passes in vacuum

Vacuum installation currently under construction (end of April)

First extraction (single shot) scheduled end of 2014

100J+ amplifier section :

80mm laser beam diameter

same parameters as 10J+ stage

Currently in design phase - Installation 2015



26/27/28/ March 2014

HEC-DPSSL

Lady Margaret Hall, Oxford